



Waterborne epoxy emulsion

1. Description

The waterborne epoxy emulsion is a milky white waterborne resin with excellent anti-corrosion performance and excellent stability qualitative, low VOC content and other excellent properties, widely used in container coatings, metal anti-corrosion coatings, and in civil anti-corrosion coatings.

2. Product parameters

Test items	Indexs	Units
Appearance	Milky white liquid	/
Solid Content	50±2	%
Epoxy equivalent	900-1100	g/mol
Viscosity (25 °C)	300-3000	MPa · s

3. Product packaging

This product is packaged in 220kg sealed iron drums and is not a hazardous material

4. Storage and precautions

- 1) Epoxy resin should be stored in a cool and dry place, avoiding rain and sunlight exposure.
- 2) When mixing epoxy resin, it is necessary to use it as needed and mix the curing agent appropriately to avoid waste.
- 3) The storage period of epoxy resin is generally 1 year. If it exceeds the storage period, it should be tested. If it meets the indicators, it can still be used.



东海岸化学集团
DK EAST COAST

Disclaimer

All recommendations for use of our products whether given by us in writing, verbally or to be implied from the results of tests carried out by us are based on the current state of our knowledge. Although, the information contained in this sheet is accurate, no liability can be accepted in respect of such information. We warrant only that our product will meet the designated specifications and make no other warranty either express or implied, including any warranty of merchantability or fitness for a particular.